

VINYL GLOVE

POWDERED & POWDER-FREE



Functional Benefits

- Intrinsic softness reduces hand fatigue even for long hours of wearing these gloves, due to low 100% modulus 25 kg/cm² comparing with normal commercial product at 3 kg/cm²; super flexibility and light weight.
- Double layers of PVC/PU films to provide double protection.
- · Odor free, results from special formulations.
- Ease in donning due to the excellent slippery inner surface.
- In grip from slightly tacky outer surface.



VINYL GLOVE

POWDERED & POWDER-FREE

Quality Standards

· Conforms to ASTM D5250 and EN455 Standards

Glove Sizes

- Extra Small, Small, Medium, Large, Extra-Large
- · Marked in the check box on the shipping carton with black ink

Product Specifications

Type Powdered or Powder-free and non-sterile

Material Polyvinyl Chloride paste resin, Grade: FPC DNV2P

Design & Features Ambidextrous, beaded cuff; clear or coloured (blue)

Storage The gloves shall maintain their properties when stored in a

dry condition at temperature between 10 to 30°C.

Protect gloves against ultra violet light sources, such as

sunlight and oxidizing agents. Copper ions discolor the glove.

Shelf-life 5 years from date of manufacturing

Physical Dimensions

DIMENSIONS	STANDARDS	
	Top Glove	ASTM D5250-06
Length (mm) Minimum	230 min	230 mm for all sizes
Width (mm) • Extra-small • Small • Medium • Large • Extra-large	75 ± 5 85 ± 5 95 ± 5 105 ± 5 115 ± 5	85 ± 5 95 ± 5 105 ± 5 115 ± 5
Thickness - Single Wall (mm) • Fingers • Palm	0.05 min 0.08 min	0.05 min 0.08 min

Physical Properties

Property	ASTM D5250
Elongation at break (%)	Min 300
Tensile Strength (MPa)	Min 11



International Quality System Certificate Awarded















If you have any enquiries on our products, please contact:

TOP GLOVE GROUP OF COMPANIES

Lot 4969, Jalan Teratai, Batu 6, Off Jalan Meru 41050 Klang, Selangor Darul Ehsan, Malaysia

Tel : +603-3392 1992 / 1905 Fax : +603-3392 1291 / 8410 Email : sales@topglove.com.my Website : www.topglove.com.my