

PILOT

HIGH STANDARD PROTECTION

The flexible frame is highly adaptable for unbeatable comfort.



PILOPSI


84 g

- + VERY FLEXIBLE FRAME**
- + INTERCHANGEABLE LENS**
- + ADJUSTABLE STRAP**
- + FITS OVER PRESCRIPTION GLASSES**
- + ANTI-STATIC**

bollé
SAFETY

PILOT

HIGH STANDARD PROTECTION

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
PILOT	Ventilated	PILOPSI	☞ 1 9 BT €€	☞ EN166 3 4 9 BT €€	Anti-scratch/anti-fog

LENS MARKING

Optical class symbols:

1. Continuous work

Use symbols:

9. Molten metal and hot solids.

Mechanical strength symbols:

B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

€€ European standard ☞ Manufacturer name

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

3. Liquid droplets or splashes.

4. Large dust particles > 5 microns.

9. Molten metal and hot solids.

B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

€€ European standard ☞ Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly with a mild soap detergent or optical solution.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

CONDITIONNEMENT ET GENCOD EAN13	
	PILOPSI
Individual plastic bag	3660740003524
5 spare lenses per bag	3660740103521
65 safety goggles or 90 spare lenses per outer pack	3660740203528

CHARACTERISTICS	
LENSES	PC - 2,1 mm - Curve 6
FRAME	PP + TPV
TEMPLES	Non applicable
STRAP	Nylon
FOAM	No
SPARE LENSES	No



01/10/2013

Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle
SAFETY