

FLIP-UP FACE SHIELD

Users will be thrilled by the lightness and design of this flip front protector. The RELRSI version is anti-fog acetate with a thickness of 1.5 mm that will protect you against short circuit electric arcs.



200 g



RELRSI



FARELRSI



RELPSI













FARELPSI

- + POLYPROPYLENE**
- + ADJUSTABLE HEADBAND**
- + PROTECTION AGAINST SHORT CIRCUIT ELECTRIC ARCS (RELRSI VERSION)**
- + 19 CM X 29 CM FL IP-UP FACE SHIELD**

bolle
SAFETY

FLIP-UP FACE SHIELD

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
PROTECTEUR RELEVABLE	 Acetate lens	RELRSI	2C-1,2  2 B 8 N C€	 EN166 3 8 B C€	Anti-fog (N)
	 Spare acetate lens	FARELSI	2C-1,2  2 B 8 N C€	-	Anti-fog (N)
	 Polycarbonate	RELPSI	 1 F C€	 EN166 3 8 B C€	Anti-scratch/Anti-fog
	 Spare polycarbonate lens	FARELPSI	 1 F C€	-	Anti-scratch/Anti-fog

LENS MARKING

Optical class symbols:

1. Continuous work
2. Intermittent work


Use symbols:

8. Electrical short circuit arc

Mechanical strength symbols:

- B.** Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s
- F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s

Others symbols:

- N.** Resistance to fogging (optional)
- C€ European standard  Manufacturer name


FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

3. Liquid droplets or splashes

8. Electrical short circuit arc

B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s

C€ European standard  Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly with a mild soap detergent or optical solution.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

PACKAGING AND EAN 13 CODE				
	RELRSI	FARELSI	RELPSI	FARELPSI
Individual plastic bag	3660740001957	3660740001520	3660740003487	3660740003494
50 face shields or 250 spare lenses per outer pack	3660740201951	3660740201524	3660740203481	3660740203498

CHARACTERISTICS	
LENSES	Acetate - 1,5 PC - 1,0 mm
FRAME	PP
TEMPLES	Non applicable
STRAP	Non applicable
FOAM	Non applicable
SPARE LENSES	FARELSI / FARELPSI



01/10/2013

Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle
SAFETY